

Miriama Pinosova¹⁾
Beata Hricova¹⁾
Alexandra Goga
Bodnarova¹⁾

1) Faculty of Mechanical
Engineering, Technical Uni-
versity of Košice, Slovak
Republic,
m.p.tuke@gmail.com

METHODOLOGY OF COMPREHENSIVE QUALITY EVALUATION OF THE WORKING ENVIRONMENT

Abstract: *This contribution is devoted to the experimental proposal of the methodology for a comprehensive assessment of the working environment quality. Because recent development raises the need to know as much as possible about living and working environments, thoroughly learn the working conditions and all factors that affect health therefore is also necessary to select such evaluation procedures, which would reduce as much as possible the negative effects of these factors on workers. Health at work and healthy working conditions are among the highest rated assets of individuals, communities and states.*

Keywords: *Proposal of the methodology, Quality working environment, Mathematical methods.*

1. INTRODUCTION

Risk assessment is the **process of qualitative and quantitative risk assessment** for occupational health and safety of workers. The more negative factors applied to the working environment, the greater the negative effects on the human organism. In assessing the working environment are used various methods and procedures designed to assess the possibility of harm. Therefore it is necessary to choose a suitable complex multi-criteria method, which, according to obtained information could determine the size of load of a man within the working environment. Selection criteria for assessment are not simple, because there are many indicators that characterize the working environment load. Before the assessment method is determined, it is appropriate to combine qualitative and quantitative assessment, thereby establishing a system for measurement of working environment, taking into account: *the nature of the impacts of the working environment parameters, duration of the impact, the range of risk fac-*

tors operating simultaneously, and the magnitude of the impact of individual parameters of the working environment.

With the mathematical formulation can be reached the target state, which is the idea of a display of the objective complete working environment quality in the spatial coordinates that define the different views, approaches and needs of the specification of the working environment parameters. In the designing of an experimental methodology of a comprehensive assessment of the quality of working environment we will build on the condition that the worker is affected during his work at different job positions by various risk factors. These factors vary by their intensity and duration on which depends their influence on human organism. To quantify these effects is difficult because: [1]

- Each parameter in the working environment **requires a different approach** in analysing its effect on humans,
- Each parameter has a **wide range of effects**,

- The impact of individual risk factors **varies with time and change of working activity**,
- The perception of the effects of the working environment is significantly an **individual matter**.

It is important to determine also whether the environment will be evaluated by one criterion or we have more criteria available. In our case we propose to deal with the evaluation of multiple criteria simultaneously. We propose the following evaluation procedure:

- Selection of the methods of the working environment quality assessment,
- Selection and measurement of the risk factors,
- Determining the weights of criteria (Saaty method and calculation by the software SANNA),
- Normalisation of the measured values,
- Calculation of the total load,
- Risk assessment (determination of the risk acceptability).

2. DETAILED EVALUATION PROCEDURE

2.1 Selection of the methods of the working environment quality assessment

Methods of decision making in general, present the summary of rules and procedures, using which we can come to choosing the best solution. The current situation offers us a wide range of methods of decision making. If we use a distribution based on mutual relation of empiricism and theory contained in the individual methods, it is possible to divide them into three groups of empirical, heuristic and exact methods. [2]

In solving practical problems such as the comprehensive assessment of the working environment quality is appropriate to use one of the following methods of

multi-criteria decision making. Specific methods, which can be used by a comprehensive assessment, can be as follows: *point method of assessment, proportion index method, Decision Matrix Method - DMM, Forced Decision Matrix Method - FDMM, Analytic Hierarchy Process - AHP, method of quantitative comparison - Fuller method, ranking method, etc.*

The specified methods of multi-criteria decision making vary mainly according to how they determine so called weight of individual criterion. The comprehensive assessment of working environment quality to determine the weights of the criteria we use one of the exact methods and the analytical multilevel evaluation method AHP, which provides a framework for effective decisions in complex decision making situations, it helps simplify and accelerate the natural process of decision making process. [3, 4]

2.2 Selection and measurement of the risk factors

By the comprehensive assessment of the working environment is evaluated the interaction of all risk factors. In this case enter the process the workplace factors: noise, vibration, lighting, air purity, or dust, electromagnetic fields, ergonomics, radiant heat, physical stress, hygienic factors and safety factors. The most important step is the selection and evaluation will be based on an evaluation of information of interviewed people and also from expert opinions. The next step of a comprehensive evaluation is the measurement of risk factors. The results should then be processed to evaluate and draw conclusions from them.

2.3 Selection and measurement of the risk factors

The AHP method provides a comprehensive and coherent approach to structuring the problem to quantify the elements that relate to the overall objectives and for evaluating the alternative solutions. Before

the application of the method, the valuation entity must define any criteria on the basis of which the evaluation will be conducted. [5]

This method is based on pairwise comparisons of the degree of significance of individual criteria. The evaluation is based on so called expert estimation, by which the experts in the field can compare the mutual effect of two factors. These evaluate on the basis of the scale [equal - weak - moderate - strong – very strong], and to this wording evaluation corresponds following values [1 - 3 - 5 - 7 - 9]. [6]

The pairwise comparison the two criteria are placed in the opposite ends of the line against each other and compared, which is more important. In the middle of the line is number 1, which means that the compared criteria are equally important. Along the line are the numbers 1 to 9, where the number 9 means that the criterion on the relevant end was more important than at the other end criterion. In this case, the form for the evaluation are indicated two options (strong and very strong predominance of factor B over factor A), and as the resulting assessment will appear in the line of the factor B and the column of the factor A the value „8“, and in the line of the factor A and the column of the factor B will be indicated the inverse value i.e. the value „1/8“. If *n* is the total number of elements, which are compared, then the number of comparisons is [5] (Saaty, 1985)

Further procedure for determining the weights of criteria is more complicated than other methods because it is necessary:

- For each pairwise comparison matrix to determine a normalised self-vector corresponding the maximum real self-worth (number) matrix, as considered in an absolute value,
- Its components which accordingly determine the weights of criteria and the resulting evaluation can be reached the same way as the

weighted sum of the determined evaluations multiplied by the weights of criteria.

In the Table 1 are shown the weights of criteria determined by Saaty's method of evaluation.

Table 1 - Saaty's method of weight criteria estimation

s(i,j)	Criteria					R(i)	Weight
Criteria	K1	K2	K3	K4	a(i,j)	[a(i,j)] ^{1/4}	v(i)
K1	1	3	4	5	60	1	0,5462
K2	1/3	1	2	3	2	0,4253	0,2323
K3	1/4	1/2	1	2	1/4	0,2521	0,1377
K4	1/5	1/3	1/2	1	1/30	0,1533	0,0837
Total						1,8307	1,0000

2.4 Application of the software SANNA

Calculation of the vector of weights from the paired comparison matrix is usually part of the special programs implemented by AHP method. The calculation is also possible to realise in Excel with the utilisation of so called Wielandt theorem. This mathematical theorem states that for a vector of weights reciprocal pairwise comparisons matrix is valid:

$$\lim_{r \rightarrow \infty} \frac{S^r \cdot e}{e^T \cdot S^r \cdot e} = c \cdot v$$

The relation states that the vector formed by sums of row elements r-squared matrix S divided by the sum of all elements of this matrix is close enough for sufficiently large r of the self-vector of the matrix S corresponding to the largest self-number. In individual interact will be calculated the relation (Sr.e)/ (eT.Sr.e) for r = 1, 2, 4, 8 ... and it is followed how the calculated vectors differ in two consecutive interacts. We can achieve the sufficient accuracy at r = 16. [7, 8]

Such mathematical calculation is used also by the software SANNA (Fig. 1) – System for Analysis of Alternatives. The application utilises five methods of assessment (TOPSIS, WSA, ELECTRE I, PROMETHEE II and MAPPAC) and enables to determine the weights by three methods (Point method, Fuller's method and Saaty's procedure) and to solve multi-

criteria problems by seven methods (TOPSIS, WSA, ELECTRE I, ELECTRE III, PROMETHEE II, ORESTE and MAP-PAC). With SANNA it is possible to solve up to 100 variations and 50 criteria. [9]




Figure 1 - SANNA: Saaty's calculation of weight criteria

2.5 Normalisation of the measured values the interval <0, 1>

Table 2 - Procedure of calculation of the factor values of the working environment at n-workplace or valid for n-worker

Factors of the working environment	Normalised weight of a vector	Workplaces						Evaluation of each factor at all workplaces	
		1	2	j	n			
Factor 1	v_1	F_{11}	f_{11}	F_{12}	f_{12}	F_{1j}	f_{1j}	F_{1n}	f_{1n}
Factor 2	v_2	F_{21}	f_{21}	F_{22}	f_{22}	F_{2j}	f_{2j}	F_{2n}	f_{2n}
.....									
Factor i	v_i	F_{i1}	f_{i1}	F_{i2}	f_{i2}	F_{ij}	f_{ij}	F_{in}	f_{in}
.....									
Factor m	v_m	F_{m1}	f_{m1}	F_{m2}	f_{m2}	F_{mj}	f_{mj}	F_{mn}	f_{mn}
Evaluation of all parameters according to workplaces			1		2		j		n

Real load of the working environment by the safety factors we can express in following relation $[_{ij} = v_i \cdot F_{ij}$

Where: $[_{ij}$ – real load by the safety factors, v_i – normalised value of the vector weight, F_{ij} – measured normalised value of the

The calculation of the measured values for indicators in the interval <0, 1> can be performed on the relation

$$F_{ij} = 1 - \frac{L_H - L_A}{L_H - L_D}$$

where: F_{ij} – normalised value of the basic indicator j from the class of the factor i, L_H – upper limit value of the factor, L_D – lower limit value of the factor, L_A – actual (measured) value of the factor. [1]

2.6 Calculation of the total load

Interpretation of the final coefficient calculation evaluating the level of the working environment at a workplace or in a group of workplaces is based on Table 2 and Figure 2. Manual calculation is appropriate to process according to the procedure set in Table 2.

safety factors.

The average value of the load by individual indicators $[_p$, which is the indicator of the average load of the whole working environment we can state as follows

$$[p]_j = \frac{\sum_{j=1}^n [L_j]}{n}$$

Where: j – are the elements of the column vector.




Figure 2 - Procedure of the calculation of the working environment factor values at the n-workplace

3. RISK ASSESSMENT

If the **risk (R)** is the probability of formation and at the same time the severity of consequences or adverse event, we state that the risk is the function of two basic parameters: **probability (p)** and **consequence (C)**. Mathematically expressed: **R = p x C**. And the symbol **x** expresses the type of function according to the type of evaluation (it can be a matrix or conjunction). In our opinion, a straightforward risk assessment process in five steps is suitable: **Step 1: Identifying hazards and persons at risk, Step 2: Risk assessment and prioritizing, Step 3: Deciding on preventive measurements, Step 4: Taking action, Step 5: Monitoring and control.** Choice of approach to the assessment will depend on the **nature of the workplace** (e.g. stable or temporary operation), the **type of**

process (e.g. repetitive activities, developing/changing processes, work on the contract), the **task being performed** (e.g. repetitive, occasional or high risk) and **technical complexity**. [10]

Criteria of system safety evaluation and risk assessment are not firm. As accepted risk is considered the risk which the persons in concern taking into account all operational and human conditions will be willing to bear. In our case, the risk assessment method was selected the point method. Compared to the classical definition of risk is by the assessment of the risk level utilized the expanded definition of the risk in the following form:

$$\mathbf{R} (\text{risk}) = \mathbf{p} (\text{probability}) \times \mathbf{C} (\text{consequence}) \times \mathbf{W} (\text{effect of the safety and health at work}) \times \mathbf{E} (\text{period of exposition})$$

Where: **p** – probability we determine on the basis of the Gauss function of the density of the probability normal distribution and overall load of the working environment adapted for our case study.

$$\text{and: } p = 5 - \frac{1}{0,1\sqrt{2}} e^{-\frac{([-0,5])^2}{2,0,1^2}}$$

then:

$$\mathbf{R} = 5 - \frac{1}{0,1\sqrt{2}} e^{-\frac{([-0,5])^2}{2,0,1^2}} \times \mathbf{D} \times \mathbf{V} \times \mathbf{E}$$

Risk – final indicator, which is the product of the four values of risk parameters. The lowest value can be 1 and the highest 625. The score range is classified into five risk categories according to the points: **insignificant, negligible risk; acceptable, less significant risk; adverse risk; significant risk and unacceptable risk.**

ceptable, less significant risk; adverse risk; significant risk and unacceptable risk.

4. CONCLUSION

Comprehensive evaluation of the environmental quality is a new innovative approach for assessing the effects on humans. It should be noted that this issue is complicated and therefore there are many approaches to its solution. The methodology presented in this paper describes the authors' idea about how to resolve this issue. The presented results are based on past experience in the field of measurement and evaluation of environmental factors, the authors actually perform.

REFERENCES:

- [1] Lumnitzer, E., Badida, M., Romanová, M., *Hodnotenie kvality prostredia*. Elfa s.r.o., Košice 2007. ISBN 978-80-8073-836-5
- [2] Máca, J., Leitner, B., *Opera ná analýza I. Deterministické metódy opera nej analýzy*. 2. vydanie. Žilinská univerzita. Žilina 2002. ISBN 80-88829-39-9
- [3] Ramík, J., *Vícekritériální rozhodování - Analytický hierarchický proces (AHP)*, Karviná: Slezská univerzita, 1999. ISBN 80-7248-047-2
- [4] Hnilica, R., *Development of framework for assessment of combined effects of risk factors*. Acta Facultatis Technicae. Zvolen 2 (2011) ISSN 1336-4472
- [5] Rohá ová, I., Marková, Z., *The Analysis of AHP method and its potential use in logistics*. Acta Montanistica Slovaca. Ro ník 14. 2009. íslo 1 103-112. ISSN 1335-1788
- [6] "Viacriteriálne (multikriteriálne) rozhodovanie (rozhodovacia analýza)" Retrieved from: http://fsi.uniza.sk/01_VR_1.pdf
- [7] Korviny, P., *Teoretické základy vícekritériálního rozhodování*. Dostupné na: http://korviny.cz/teorie_mca.pdf
- [8] Ramík, J., "Analytický hierarchický proces (AHP) a jeho možnosti uplatnění při hodnocení a podpoře rozhodování" *Sborník příspěvků z konference Matematika v ekonomice*. Vydání: První. Jihlava 2010 ISBN 978-80-87035-34-4
- [9] Mašátová, J., Výběr vhodného softwaru z pohledu vícekritériálního rozhodování. Diplomová práce. Vysoká škola ekonomická v Praze. Fakulta informatiky a statistiky, 2011.
- [10] *Ako vykonáva hodnotenie rizík*. Retrieved from: <http://osha.europa.eu/>

Acknowledgment: The author would like to thank to the Ministry of Education of the Slovak Republic for their financial support on the grant project VEGA 1/1216/12 – Research and development of application procedures for the solution of acoustic design of mechanical-engineering products. This work was supported by the Slovak Research and Development Agency under the contract No. APVV-0432-12.

